



Comfort solutions for all your needs



Residential



Light Commercial



Commercial

daikin-ksa.com

Rooftop Unit | DP-DC Series



Daikin Air Conditioning Saudi Arabia

Riyadh Sahafa Area | King Abdulaziz Road | Sheeha Center | Tel: +966 11 510 8500

Jeddah Al Rawdah | Prince Saud Al Faisal Street | AlTaher Tower | 6th Floor | Tel: +966 12 511 6360

Dammam Ash Shatea District | Prince Mohammed bin Fahad St | Al Shatea Business Center | 4th Floor | Tel: +966 13 808 1312

Toll Free: 800 111 0909 | info@daikin-ksa.com | www.daikin-ksa.com

DKSA-DP, DCC | JULY-2019

Follow us @DaikinSaudi



The present publication is drawn up by way of information only and does not constitute an offer binding upon Daikin Air Conditioning Saudi Arabia LLC. No express or implied warranty is given for the completeness, accuracy, reliability or fitness for particular purpose of its content and the products and services presented therein. Specifications are subject to change without prior notice. Daikin Air Conditioning Saudi Arabia LLC explicitly rejects any liability for any direct or indirect damage, in the broadest sense, arising from or related to the use and/or interpretation of this publication. All content is copyrighted by Daikin Air Conditioning Saudi Arabia LLC.



R-410A



**SINGLE-PHASE
PACKAGED AIR CONDITIONER
3,4 & 5 TONS**

Standard Features

- R-410A chlorine-free refrigerant
- Energy-efficient compressor with internal relief valve
- Variable-speed ECM indoor blower motor
- All-aluminum evaporator coil
- Copper tube / aluminum fin condenser coil with coating
- Totally enclosed, permanently lubricated condenser fan motor
- Fully charged system
- AHRI Certified; ETL listed

Cabinet Features

- Heavy-gauge galvanized-steel cabinet with attractive - Nickel Gray powder-paint finish
- Compressor sound blanket
- Fully insulated blower compartment with convenient access panels
- Louvered condenser coil protection
- One footprint; three heights

Accessories

- Electrical Heat Kits available as factory-installed or field-installed accessories

MODEL DP15CH COOLING				DP15CH364A	DP15CH484A	DP15CH604A
Tonnage				3.0	4.0	5.0
Cooling Capacity	Nom.	Btu/H	35,600	46,000	57,500	
Power Input	Nom.	Cooling Watts	3080	3690	5010	
EER	Nom.	Cooling Btu/W	12.00	12.00	12.00	
Evaporator	Air Flow Rate	Cooling CFM	1,200	1,600	1,600	
External Static Pressure			Pa			25 - 225
Condensation Drain Size			OD	Inch		3/4"
Dimensions			WxHxD	Inch		66 x 30.5/33 66 x 35.5/33 66 x 35.5/33
			cm			165 x 76 x 82.5 165 x 88.7 x 82.5 165 x 88.7 x 82.5
Shipping Weight			Kg			146 168 171
Operation Range			Cooling	°CDB		2 to 52 °C
Sound Power Level	Nom.	dB		78	80	
Power Supply	Voltage/Phase/Frequency	V/Ph/Hz	208/230-1/60	208/230-1/60	208/230-1/60	
Supply/Return Duct Connection			Horizontal			Horizontal Horizontal Horizontal

* for any additional technical data please refer to the engineering data book or Daikin offices



**THREE-PHASE
PACKAGED AIR CONDITIONER
7.5, 15, & 25 TONS**

Standard Features

- R-410A chlorine-free refrigerant
- High-efficiency scroll compressor
- Copper tube / aluminum fin condenser coil with coating
- High-and low pressure switches
- High-capacity, steel-cased filter drier
- Built-in filter rack with standard 2" filters
- Heater kits with single-point entry
- Crankcase heaters
- Power block for field wiring
- 24-volt terminal strip
- Easy to service
- AHRI Certified; ETL listed

Cabinet Features

- Heavy-gauge, galvanized-steel cabinet with UV-resistant powder-paint finish
- Full perimeter rail
- Sloped drain pan

Accessories

- Electrical Heat Kits available as factory-installed or field-installed accessories

MODEL DPCC COOLING				DDC090*6B*A	DDC180*6B*A	DDC300*6B*A
Tonnage				7.5	15	25
Cooling Capacity	Nom.	Btu/H	90,000	180,000	290,000	
Power Input	Nom.	Cooling Watts	7800	16210	28700	
EER	Nom.	Cooling Btu/W	11.50	11.20	10.40	
Evaporator	Air Flow Rate	Cooling CFM	3,000	5,875	8,000	
External Static Pressure			Pa			25 - 275 50 - 300
Condensation Drain Size			OD	Inch		3/4" 1"
Dimensions			WxHxD	Inch		1100 x 23 x 61.7 133 x 50.7 x 88 133 x 50.7 x 88
			cm			250 x 57.5 x 154 332 x 127 x 220 332 x 127 x 220
Shipping Weight			Kg			493 945 1080
Operation Range			Cooling	°CDB		2 to 52 °C
Sound Power Level	Nom.	dB		82	88	92
Power Supply	Voltage/Phase/Frequency	V/Ph/Hz	400/3/60	400/3/60	400/3/60	
Supply/Return Duct Connection			Convertible	Bottom	Bottom	

* for any additional technical data please refer to the engineering data book or Daikin offices