

Wall mounted unit

FXAQ-PV/FXAQ-PVER



Whisper quiet



Vertical auto swing



Multi tenant

- › Ideal solution for commercial spaces with no or narrow false ceilings
- › Can easily be installed in both new and refurbishment projects
- › Flat, stylish front panel blends easily within any interior décor and is easier to clean
- › The air is comfortably spread up- and downwards thanks to 5 different discharge angles that can be programmed via the remote control
- › Maintenance operations can be performed easily from the front of the unit

FXAQ-PV/FXAQ-PVER




FXAQ20-32PV

Indoor unit		FXAQ-PV/FXAQ-PVER	20PV	25PV	32PV	40PVER	50PVER	63PVER	
Cooling capacity	Nom.	kW	2.2	2.8	3.6	4.5	5.6	7.1	
Heating capacity	Nom.	kW	2.5	3.2	4.0	5.0	6.3	8.0	
Power input - 50Hz	Cooling	Nom.	kW	0.019	0.028	0.030	0.020	0.033	0.050
	Heating	Nom.	kW	0.029	0.034	0.035	0.020	0.039	0.060
Dimensions	Unit	Height	mm	290					
		Width	mm	795		1,050			
		Depth	mm	238					
Weight	Unit	kg	11			14			
Casing	Colour	White (3.0Y8.5/0.5)							
Fan-Air flow rate - 50Hz	Cooling	High/Low	m ³ /min	7.5/4.5	8/5	8.5/5.5	12/9	15/12	19/14
Air filter	Type	Washable resin net							
Sound power level	Cooling	Nom.	dBA	-					
Sound pressure level	Cooling	High/Low	dBA	35.0/31.0	36.0/31.0	38.0/31.0	39.0/34.0	42.0/37.0	47.0/41.0
	Heating	High/Low	dBA	35.0/31.0	36.0/31.0	38.0/31.0	39.0/34.0	42.0/37.0	47.0/41.0
Refrigerant	Type	R-410A							
	GWP	-					2,087.5		
Piping connections	Liquid	OD	mm	6.35				9.52	
	Gas	OD	mm	12.7				15.9	
	Drain	VP13 (I.D. 13/O.D. 18)							
Power supply	Phase/Frequency/Voltage	Hz/V	1~/50/60/220-240/220						
Current - 50Hz	Maximum fuse amps (MFA)	A	15						
Control systems	Infrared remote control	-							
	Wired remote control	-							
	Simplified wired remote control for hotel applications	-							

Contains fluorinated greenhouse gases

Daikin Europe N.V. Naamloze Vennootschap · Zandvoordestraat 300 · 8400 Oostende · Belgium · www.daikin.eu · BE 0412 120 336 · RPR Oostende (Responsible Editor)



ECPEN16-261

03/16



The present leaflet is drawn up by way of information only and does not constitute an offer binding upon Daikin Europe N.V. Daikin Europe N.V. has compiled the content of this leaflet to the best of its knowledge. No express or implied warranty is given for the completeness, accuracy, reliability or fitness for particular purpose of its content and the products and services presented therein. Specifications are subject to change without prior notice. Daikin Europe N.V. explicitly rejects any liability for any direct or indirect damage, in the broadest sense, arising from or related to the use and/or interpretation of this leaflet. All content is copyrighted by Daikin Europe N.V.